



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 1 of 7

Date of Issue: 12/03/2014

Version no.1

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

Product name: Beger Teak Oil #1000

Supplier: Beger Co., Ltd.

Address: 90, 92 Buntudthong Road, Thanon Petchaburi, Ratchathawi, Bangkok 10400 Thailand.

2. COMPOSITION / INFORMATION ON INGREDIENTS

No.	Description	UN Number	CAS.No.	R-Phrases	Weight (%)
1	Mineral Spirit	1300	64742-82-1	65-51/53	>15-20
2	Turpentine Oil	1300	64742-95-6	65-51/53	>10-25

* No other material added intentionally after than shown above.

Legend: T+=Very toxic, T=Toxic, C=Corrosive, Xn=Harmful, Xi=Irritant, IK=No classification required, E=Explosive, O=Oxidizing, F+=Extremely flammable, F=Very flammable, Fo=Flammable, N=Danger to the environment.

3. HAZARDS IDENTIFICATION

Inhalation: Slightly irritant.

Skin Contact: Prolonged or repeated skin contact can cause slight skin irritation.

Eye Contact: Direct contact with material can cause slight irritation.

4. FIRST AID MEASURES

General Advice: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Remove patient to fresh air and seek medical assistance. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position.

Skin Contact: Remove contaminated clothing. Wash skin with soap and water. Rinse abundantly.

Eye Contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Ingestion: Immediately rinse mouth and then drink a plenty of water. Do not induce vomiting. Keep patient warm and at rest and call a doctor immediately.



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 2 of 7

Date of Issue: 12/03/2014

Version no.1

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Foam (alcohol resistant), carbon dioxide, powders, water spray. Do not allow run-off from firefighting to enter drains or watercourses.

Unsuitable Extinguishing Method:

Water Jet.

Special Hazards due to the Substance, its Decomposition Products or Gases Produced by Fire:

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Special Protective Equipment:

Appropriate breathing apparatus may be required.

Additional Information:

Cool closed containers in the vicinity of the source of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal Protective Measures:

Refer to protective measures listed in sections 7 and 8.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours.

Measures to Protect the Environment:

Do not allow to enter drains or watercourses. If the product enters drains or sewers, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Cleaning Measures:

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents.



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 3 of 7

Date of Issue: 12/03/2014

Version no.1

7. HANDLING AND STORAGE

Handling:

Instructions for Safe Handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Isolate from sources of heat, sparks and open flame. Do not use any sparking tools.

Information on Fire and Explosion Protection

Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. Keep container dry and tightly closed in a cool well-ventilated place.

Storage:

Requirements for Storage Areas and Containers

Floors must be of conducting type and impermeable to the materials being stored.

Keep container tightly closed. Never use pressure to empty; container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. No smoking. Prevent unauthorized access.

Information on Combined Storage Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Additional Information on Storage Conditions

Always keep in containers of same material as the original one. Observe label precautions. Store in a well-ventilated place away from source of heat and direct sunlight. Keep away from sources of ignition.

Storage Temperature: 5-35°C.



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 4 of 7

Date of Issue: 12/03/2014

Version no.1

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Measures: Provide adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentration at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal Protection:

Respiratory Protection. When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Suitable respiratory protection: e.g. half-mask with A2P2 class combination filter.

Hand Protection.

Necessary for prolonged or repeated contact. Suitable protective glove: e.g. nitrile gloves. The protective glove type should always be tested for its suitability (e.g. antistatic, mechanical and chemical resistance etc.).

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye Protection.

Required when there is a risk of eye contact. Use tight-fitting protective goggles.



HYGIENE PRACTICES: Good personal hygiene practices are required at all times when handling chemicals. These practices including, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks and especially of contamination occurs.



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 5 of 7

Date of Issue: 12/03/2014

Version no.1

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Liquid
Colour:	Yellowish
Odour Characteristic:	Specific
pH Value:	Not Applicable
Change in Physical State:	
Boiling Temperature/Range:	n.d.a.
Melting Point/Range:	n.d.a.
Flash Point:	38-42°C
Ignition Temperature:	>200°C
Explosion Limits,	
Lower:	n.d.a.
Upper:	n.d.a.
Vapour Pressure:	n.d.a.
Density:	0.875 g/cm ³ at 20°C
Solubility in Water:	Immiscible

10. STABILITY AND REACTIVITY

Conditions to be avoided.

Substances to be avoided.

Hazardous Decomposition Products.

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Skin and mucous membrane compatibility, rabbit: Skin 4 hours exposure-slightly irritant.

Eyes: Non-irritant (Tested according to OECD Guide Guidelines No.404 and No.405).

Long term contact with skin: Tanning and irritating effects are possible.

Over-exposure, especially during spraying operations without the necessary precautions, entails the risk of concentration-dependent irritating effects on eyes, nose throat, and respiratory tract.

The liquid splashed in the eyes may cause irritation and reversible damage.



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 6 of 7

Date of Issue: 12/03/2014

Version no.1

12. ECOLOGICAL INFORMATION

The product should not be allowed to enter drains or water courses.

Do not allow escaping into water, wastewater or soil.

13. DISPOSAL CONSIDERATIONS

Waste form residues / unused products:

Solidify unexposed surplus and dispose of together with processed material as cured plastic waste – in accordance with local and national regulations.

Contaminated packing:

In accordance with local and national regulations.

14. TRANSPORT INFORMATION

Transport by Road or Rail.

UN 1263, Paint, 3, II, ADR/RID

(Vapour pressure at 50°C not more than 110 kPa).

Hazard identification number 33.

Sea Transport.

Paint, 3, UN 1263, II

Air Transport.

Paint, 3, UN 1263, II

Additional Information.



MATERIAL SAFETY DATA SHEET

Product Name: Beger Teak Oil

Product Code: 1000

Page 7 of 7

Date of Issue: 12/03/2014

Version no.1

15. REGULATORY INFORMATION

The product is classified and labeled for supply in accordance with the EC directives. (1999/45/EC).

Danger Symbol: -

Danger Classification: Harmful Flammable.



Product Contains:

Mineral Spirit

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritation to skin.

Labeling for Industrial Users.

S16: Keep away from sources of ignition-No smoking.

S23: Do not breathe spray dust/solvent vapour.

S33: Take precautionary measures against static discharges.

S36/37: Wear suitable protective clothing and gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

National Regulations.

16. OTHER INFORMATION

Restricted to professional users.

Full text of risk warnings for components listed in section 2.

R10: Flammable.

R11: Highly flammable.

R20: Harmful by inhalation.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

This information contain herein relates only to the specific material identified. The company believes than such information is accurate and reliable as of the date of this safety date sheet, but no representation, guaranty, expressed or implied, is made as to the accuracy, or completeness of the information.