



BEGER ACRYLIC ALKALI RESISTING PRIMER #B-11050

Acrylic Alkali Resisting Primer : Exterior & Interior Primer

Description	<p>Beger Acrylic Alkali Resisting Primer #B-11050, acrylic alkali resisting primer is high quality emulsion paint for priming masonry, which the new surface to blocked alkali and efflorescence and promoting good adhesion to Beger 100% Acrylic Emulsion.</p> <p>No added lead and no added mercury.</p>		
Feature and Benefits	<ul style="list-style-type: none"> * Easy to apply, give smooth appearance. * Excellent water and alkali resistance. * Good resistance to fungus mildew and mold attack. 		
Properties for Use	<p>Beger Acrylic Alkali Resisting Primer #B-11050, acrylic alkali resisting primer for priming masonry surfaces including new concrete and fresh cement.</p>		
Film Thickness and Spreading Rate	Minimum	Maximum	Typical
* Dry film thickness (microns)	0	0	30
* Wet film thickness (microns)	0	0	0
* Theoretical coverage rate (m ² /U.S.Gallon/coat)	35	40	Actual consumption rate depends on application method and surface condition.
Physical Properties	<ul style="list-style-type: none"> * Vehicle type : Acrylic Primer * Finish : Matt * Colour : White * Solid by volume : 38 - 42% * Dry time (@25'C, 30 mm.DFT) <ul style="list-style-type: none"> Touch dry : 30 minutes Recoat : 2 hours Dry to handle : - * Flash point : None 		
Application Method	<ul style="list-style-type: none"> * Tool : Brush, roller or spray gun. * Thinner : Clean water. * Condition during application : The moisture content in the concrete should not exceed 14%. <ul style="list-style-type: none"> : Application by airless spray : dilute with 5 - 10% clean water by volume. : Application by roller, brush and spray gun : dilute with 0 - 10% clean water by volume. : Application for spray <ul style="list-style-type: none"> * Airless spray : nozzle orifice 0.018 inches : nozzle pressure 165 atm. * Spray : nozzle orifice 1.8 - 2.0 mm. : nozzle pressure 3 - 4 atm. 		
Application System	<ul style="list-style-type: none"> * Surface preparation : Surface should be dry and clean. <ul style="list-style-type: none"> : Remove completely all dirt, grease, oil, water or any contaminated by washing surface with suitable cleaner. : Repair all surface imperfections. Before application, fill and seal hairline cracks by working a generous amount of material into void. Cracks and gaps wider than 2.0 - 10.0 mm. should be filled with acrylic sealant. Use Beger Acrylic Wall Filler #F-200 for cracks and gaps with less than 0.3 - 1.0 mm. width. : Surface with fungus, mold and mildew growth must be cleaned off and follow by the treatment of fungicidal wash Beger MouldFree #M-001. * Typical paint system : New Masonry Substrate <ul style="list-style-type: none"> * Beger Acrylic Alkali Resisting Primer #B-11050 1 - 2 coats * Beger Acrylic Emulsion Paint (Sheen) 2 - 3 coats : Previously Painted Surfaces <ul style="list-style-type: none"> * Beger Contact Primer #B-1500 1 coat * Beger Acrylic Alkali Resisting Primer #B-11050 1 - 2 coats * Beger Acrylic Emulsion Paint (Sheen) 2 - 3 coats 		
Storage	<ul style="list-style-type: none"> : The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat an ignition. : Containers must be kept tightly closed. : 12 months at ambient. 		
Health and safety	<ul style="list-style-type: none"> : Use under well ventilated conditions. : Do not breathe or inhale mist. : Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. : Eyes should be well flushed with water and medical attention sought immediately. 		
Precaution	<ul style="list-style-type: none"> : Keep out of reach of children. 		
Reference Standard	: -		
Packing Size	: 1 Gallon, 5 Gallons.		

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, We cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice. Beger Acrylic Alkali Resisting Primer #B-11050

